

## Leak Lock and Leak Lock GOLD with Teflon

A resin based soft setting brushable paste pipe joint compound resistant to all refrigerants, oils, water and most chemicals, liquids and gases.

- Use with pressures to 10,000 PSI to full vacuums.
- Temperature range -200°F (-93°C) to 400°F (204°C).
- It never hardens and it never becomes brittle.
- Ideal for joining all metals, plastics and other materials.
- Will stick to all clean surfaces.
- Prevent vibration from loosening nuts, bolts, plugs and fittings.
- Non Toxic
- GUARANTEES A PERFECT SEAL... UNDER ALL CONDITIONS



PART NO.	SIZE	PACKAGING
<b>LEAK LOCK</b>		
HS10001	1-1/3 oz TUBE	12/CASE
HS10004	4 oz Brush Top Plastic Jar	12/CASE
HS10016	16 oz Brush Top Plastic Jar	12/CASE
HS10128	1 Gallon Can	1
<b>LEAK LOCK GOLD</b>		
HS11001	1-1/3 oz TUBE	12/CASE
HS11004	4 oz Brush Top Plastic Jar	12/CASE
HS11016	16 oz Brush Top Plastic Jar	12/CASE
HS11128	1 Gallon Can	1

## Red Epoxy

When you need a sealant you can count on.

High Performance, Heat Cured, Two Part, Epoxy Kit

- Exhibits a Color Change When Cured (Turns Gold)
- May Be Cured With a Hot Air Gun or Open Flame in Minutes
- -100°F (-73°C) to 300°F (149°C)
- Working Pressure in Excess of 3000 PSI
- Tensile Strength: 6000 PSI
- Works on Vertical Surfaces
- Pressure Tested to 3000 psi
- Simple, Quick Mixing & Application
- Oil, Gas, Fuel & Solvent Resistant
- No Rush, No Wait, You Control Curing Time
- Equipment is Serviceable Immediately
- Use on All Metals and Rigid Plastics
- HVAC & Refrigeration
- Plumbing & Appliances
- Automotive & Marine
- Petrochemical, Manufacturing
- Industrial, Commercial, Institutional



PART NO.	SIZE	PACKAGING
HS12001	Kit Including 2 1/2 oz Tubes	12/CASE

## Solderlene

High Quality, Paste Type, Non-Acid Soldering Flux.

- Industrial strength wetting agents to promote solder flow
- For use with low and mid-temp. soft solders, both lead and lead-free
- Effective on all metals except aluminum and magnesium.
- Brush Top Plastic Jars



PART NO.	SIZE	PACKAGING
HS30004	4 oz	12/CASE
HS30016	16 oz	12/CASE

## Thawzone

(New Formula)

The original liquid dehydrant, frees your frozen system in minutes. It seeks out moisture and chemically bonds to it.

- Enhanced moisture control in even the most advanced systems.
- Aids with oil return in low temperature systems.
- Compatible with all refrigerants and refrigeration lubricants.
- Helps prevent the formation of acid.
- No Methanol
- Environmentally Sound
- Safer
- Biodegradable, non-polluting
- Non-Poisonous

Add 1/8 fluid ounce ( 3.75 ml ) of THAWZONE directly to the refrigerant of any system for every 1 lb. Of refrigerant in the system.

\*HIGHSIDE SYSTEM INJECTOR ( part no. HSINJ001 ) IS RECOMMENDED FOR INTRODUCING THAWZONE INTO AN OPERATING SYSTEM.



PART NO.	BOTTLE SIZE	PACKAGING
HS17001	1 oz	24/CASE
HS17004	4 oz	12/CASE